

CLIENT DEVICE INTEROPERABILITY TEST RESULTS

Document Version: v1.0		
Client Device Details		
Client Device Make	Zebra	
Client Device Type	Mobile Computer	
Client Device Model	TC52AX	
Client Device OS type	Android 11	
Tested Client Device NIC capability	11ac, 2 Spatial Stream	
Test Configuration		
Aruba OS Version	8.8.0.1 - 80393	
Access Point	AP-515	
Basic Wi-Fi Interoperability Test and Capability Results		
Feature	Support	Capability Details
Association		
Supported Encryption Opmodes	✓	Open, Mac Auth, Open WEP, PSK(TKIP/AES), Enterprise (TKIP/AES), Mixed (PSK/AES)
Channels		
2.4 GHz Radio	✓	1,6,11
5 GHz Radio	✓	36-165
Roaming		
Opportunistic Key Caching (OKC)	✓	OKC is supported
Fast Transition (802.11r)	✓	FT with both PSK and Enterprise SSID
Protocols		
BSS Transition (802.11v)	X	Not capable of BSS Transition
WMM Client (802.11e)	✓	802.11e Capable
WMM-PS (U-APSD)	✓	UAPSD Power Save Capable
Radio Resource Management (802.11k)	✓	802.11k Capable
Management Frame Protection (802.11w)	✓	MFP-Capable and MFP-Required
802.11h and 802.11d	✓	Supports DFS and TPC
WPA3 Capabilities		
OWE	✓	OWE Capable
WPA3-SAE	✓	SAE Capable
WPA3-CCM-128	✓	CCM-128 Capable
WPA3-SuiteB	✓	Suite-B Capable
WPA3-AES-GCM-256	✓	GCM-256 Capable

802.11ax Client Capabilities		
802.11ax Capable	✓	11ax Capable
DL-OFDMA	✓	Capable of receiving OFDMA frames
UL-OFDMA	✓	Capable of transmitting OFDMA frames
DL MU-MIMO	✓	This client can receive HE MU-MIMO frames
UL MU-MIMO	X	This client can't transmit HE MU-MIMO frames
TWT Capable	X	TWT is not supported
1024 QAM Capable	✓	All rates up to MCS 11 supported in both Tx and Rx
Notes and Additional Comments		

NOTE: Client Device may support a superset of the above capabilities

ABBREVIATIONS: NR: Neighbor Report; BR: Beacon Report; LM: Link Measurement, TSM: Transmit Stream Measurement, MFP: Management Frame Protection, FT: Fast Transition, OKC: Opportunistic Key Caching, DFS: Dynamic Frequency Selection, TPC: Transmit Power Control, DL: Downlink, UL: Uplink, TWT: Target Wake Time, OFDMA: Orthogonal Frequency Division Multiple Access